C-9314P

DC9000 / DI9000 Series conventional remote indicator

General

The C-9314P remote indicator is used to replicate the fire alarm indication for a fire detector and indicate it where it can be viewed easily. It is controlled directly from the detector. It is particularly suitable for viewing the status of detectors installed in places such as residential apartments or other normally inaccessible or dangerous areas such as under false floors or above false ceilings.

Application

The C-9314P indicator may be connected to any compatible detector base.



Details

- Direct two-wire connection to detector
- Large angle of visibility
- Compatible with third party products

C-9314P

DC9000 / DI9000 Series conventional remote indicator

Technical specifications

General

Compatibility	GST DC-9000E Systems

Electrical

Operating voltage	2 to 3 VDC
Current consumption	0 (Standby) ≤30 mA
Cable size	>1.0 mm²

VID

Colour	Red
Flash frequency	Constant ON
Synchronization	No

Physical

Physical dimensions	64.5 x 64.5 x 31.4 mm (W x H x D)
Colour	White
Mounting type	Ceiling mount, Wall mount
Mounting position	Ceiling, Wall
Material	ABS

Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Relative humidity	≤95%, non condensing
Environment	Indoor
IP rating	IP20

Regulatory

Compliancy	CE

Compatible products

Category	Reference	Description
Enclosures	D-92WPB	IP66 weatherproof box for DI-9204, DC-9204, DI-M9204 & DC-M9204 Manual Call Points

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 3 February 2025 - 12:32