FC-315-CA1

Wireless, white, ceiling mount SDR VAD Head only

The FC-315-CA1 is a White, fire alarm sounder/VAD combination to be used with a wireless base. The VAD lens is specifically designed to have maximum coverage in ceiling mount applications. The 32 tone device is suitable for indoor use.

The sounder is quick and easy to install into the wireless base FC-171-001 with a simple turn and lock mechanism.

Details

- Dual band 868 MHz operation
- 32 selectable tones
- 0.5 Hz or 1 Hz VAD flash selection
- Integrated audio monitoring
- Volume control possible
- Anti tamper locking mechanism
- Third party EN certified

FC-315-CA1

Wireless, white, ceiling mount SDR VAD Head only

Technical specifications

General

Wireless frequency	868 MHz
Compatibility	FC-171-001

Electrical

Power supply type	Batteries
Batteries	Powered by radio base

Sounder

Output level	< 99 dB(A) @ 1 m (Tone dependant)
Output level adjustment	Analogue
Frequency	Selectable
Selectable tones	32
No. of stages	2

VAD

Colour	White flash
Rating	C-3-15
Flash frequency	0.5 or 1 Hz

Physical

Physical dimensions	120 x 145 mm (Ø x H) - Including base
Net weight	650 g - Including base
Colour	White housing / white flash
Mounting type	Ceiling mount
Mounting position	Ceiling
Mounting base	Wireless

Environmental

Vandal proof	Yes
Operating temperature	-10°C to 55°C
Storage temperature	5°C to 30°C
Relative humidity	< 95% non-condensing
Environment	Indoor

Regulatory

Compliancy	CE
Certification	BOSEC, CPR
Standards	EN54-3, EN54-23 EN54-13

KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 2 June 2026 - 12:24