DI-9102E

GST Intelligent DI-9000E Series Addressable Optical Detector

General

The Intelligent DI-9102E optical detector uses light scattering technology combined with a high performance optical chamber making it suitable for detecting slow burning and smouldering fires. It allows for 2 different smoke sensitivity levels to be configured.

Applications

The DI-9102E is a general application detector and is therefore suitable for applications such as hotels, restaurants, office buildings, schools, banks, warehouse, libraries, computer rooms, switch rooms and many more.

Overview

The GST DI-91xxE series intelligent detectors all feature the latest GST digital loop protocol and are compatible with the GST200N and GST-IFP4E intelligent fire alarm control panels. This enhanced digital communication protocol offers the possibility for the detectors to raise an alarm within 1 second, allowing more control and better and faster processing at the CIE.

All the DI-9000E series detectors may be installed onto the common detector base and allow for the connection of a common remote indicator.



Details

- Electronic addressing safeguarding against uncontrolled address changes
- Intelligent detection algorithm for analysing optical smoke signals and recognising dark smoke quickly.
- Drift compensation allows for good environmental adaptability
- Self-diagnostic testing ensuring reliability at all times
- Chamber contamination checking and reporting
- Removable innovative sensing chamber
- Local reed-switch test activation for easy maintenance
- Alarm LED with 360° visibility
- Remote indicator output
- Configurable polling LED support
- 2 Smoke sensitivity levels
- Local event storage
- LPCB marked

DI-9102E

GST Intelligent DI-9000E Series Addressable Optical Detector

Technical specifications

General

Status indication	LED
Compatibility	GST DI-9000E systems
Alarm levels	2
Event log	14 events
Connectivity	2-wire loop & remote indicator
Addressing method	Electronic

Electrical

Power supply type	Loop powered
Operating voltage	16 to 28 VDC (24 VDC typical)
Current consumption	≤800 µA (quiescent) ≤1.8 mA (alarm)

Detection

Detection principle	Optical light scatter

Output

Output quantity	1
Remote alarm output	2 mA

Physical

Physical dimensions	100 x 44.5 mm (Ø x H)
Shipping weight	±110 g
Colour	Traffic white (RAL9016)
Mounting type	Ceiling mount
Material (body)	ABS

Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Relative humidity	≤ 95% noncondensing
Environment	Indoor
IP rating	IP2x

Regulatory

Compliancy	CE, REACH, RoHS, WEEE
Certification	CPR
Standards	EN54-7 BS5839-1 compliant

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 12 June 2024 - 6:13