

DI-9204E

Innovation Intelligent DI-9000E Series Addressable Manual Call Point

General

The DI-9204E is an intelligent digital manual call point operating on the latest digital loop protocol. It is compatible with the GST200N and GST-IFP4E intelligent fire alarm control panels where it allows a direct user interface with the fire alarm system for manual alarm reporting.

The DI-9204E is a semi-flush mount type MCP. A back box is supplied with the MCP for surface mounting.

Operation

An alarm is reported by pressing the resettable element. The alarm is confirmed by the DI-9204E by an illuminated LED. The alarm is signalled automatically to the CIE. To reset a special key is supplied with the unit.

Installation

The DI-9204E is simply connected by two wires to any compatible fire alarm zone monitor where it gets its power and reports events using the same 2 wires. The provided reset key is also used to unlock the MCP.

The DI-9204E is suitable for public places where accidental activation can be avoided by using an optional protection flip cover (D-92FC). For outdoor applications a weatherproof enclosure (D-92WPB) is additionally available.



Details

- Non-break activation with easy reset using a special key
- Advanced digital communication
- Electronic addressing
- Easy installation with plugin connector
- Easy test function
- Dual activation indication i.e. via LED and alarm flag on the face of the unit
- Surface or semi flush mount
- Protection hinged cover & outdoor mounting box available
- Approved to the latest standards, LPCB marked

DI-9204E

Innovation Intelligent DI-9000E Series Addressable Manual Call Point

Technical specifications

General

Status indication	Red LED
Compatibility	GST DI-9000E series systems
Connectivity	2-wire loop
Addressing method	Electronic

Electrical

Power supply type	Loop powered
Operating voltage	16 to 28 VDC 24 VDC (typical)
Current consumption	0.6 mA (Standby) ≤1.8 mA (Alarm)
Cable specification	>1.0 mm ²
No. of cable cores	2
Terminals	4

Detection

Detection principle	Microswitch
Coverage area	Subject to local codes
Zone length	CIE Specific

Isolation

Series resistance	470 Ω ½ W
-------------------	-----------

Physical

Physical dimensions	87.1 x 87.1 x 58.5 mm (W x H x D)
Shipping weight	160 g
Colour	Red
Mounting type	Back box, Wall mount
Cable entries	3
Material (body)	ABS
Functional marking	House of Fire

Environmental

Vandal proof	No
Operating temperature	-10 to +55°C
Relative humidity	≤95% noncondensing
Environment	Indoor
IP rating	IP43

Regulatory

Compliance	CE, REACH, RoHS, WEEE
Certification	CPR
Standards	EN54-11



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 12 June 2024 - 6:13