

SC-52-0200-0001-99

SmartCell Information Manual Call Point

Overview

The SmartCell Information Call Point is quick and easy to install and offers individual addressing at the SmartCell Control Panel. The device when activated, sends an information alert to the Control Panel.

Features include a protective transparent cover, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Quick and easy to install
- Compact enclosure
- Includes protective transparent cover
- Unique design
- Inbuilt locking mechanism
- NOT FOR FIRE APPLICATIONS

SC-52-0200-0001-99

SmartCell Information Manual Call Point

Technical specifications

General

Status indication	LED
Wireless frequency	868 MHz
Compatibility	SmartCell

Electrical

Batteries	2 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)
-----------	--

Physical

Physical dimensions	92 x 97 x 47 mm (W x H x D)
Net weight	0.2 kg
Colour	White
Mounting type	Wall mount

Environmental

Operating temperature	-10 to +55°C
Storage temperature	-10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor

Regulatory

Compliance	CE
Certification	CPR
Standards	EN54-13 R&TTE



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 30 July 2025 - 17:41