

DI-9103E

GST Intelligent DI-9000E Series Addressable Heat Detector

General

The Intelligent DI-9103E heat detector is able to offer both fixed temperature alone, or rate-of-rise temperature alarms. It analysing the environmental temperature conditions using a semiconductor heat sensor.

It supports EN54 temperature classes A1R, A2S and BS.

Applications

The DI-9103E is especially suitable to places where a flaming fire is more likely to occur forcing a sharp rise in temperature.

Overview

The GST DI-91xxE series intelligent detectors all feature the latest GST digital loop protocol and are compatible with the GST200N and GST-IFP4E intelligent fire alarm control panels. This enhanced digital communication protocol offers the possibility for the detectors to raise an alarm within 1 second, allowing more control and better and faster processing at the CIE.

All the DI-9000E series detectors may be installed onto the common detector base and allow for the connection of a common remote indicator.



Details

- Electronic addressing safeguarding against uncontrolled address changes
- Self-diagnostic testing ensuring reliability at all times
- Local reed-switch test activation for easy maintenance
- Alarm LED with 360° visibility
- Remote indicator output
- Configurable polling LED support
- 3 Programmable detection categories
- LPCB marked

DI-9103E

GST Intelligent DI-9000E Series Addressable Heat Detector

Technical specifications

General

Status indication	LED
Compatibility	GST DI-9000E systems
Alarm levels	3
Connectivity	2-wire loop & remote indicator
Addressing method	Electronic

Electrical

Power supply type	Loop powered
Operating voltage	16 to 28 VDC (24 VDC typical)
Current consumption	≤600 µA (quiescent) ≤1.5 mA (alarm)
Cable specification	> 1 mm ²

Detection

Detection principle	Heat sensitive thermistor
Sensitivity	Category A1R, A2S, BS
Alarm temperature (maximum)	+77°C
Alarm temperature (minimum)	+58°C
Rate-of-rise	Supported

Output

Output quantity	1
Remote alarm output	2 mA

Physical

Physical dimensions	100 x 53.3 mm (Ø x H)
Shipping weight	110 g
Colour	Traffic white (RAL9016)
Mounting type	Ceiling mount
Material (body)	ABS

Environmental

Vandal proof	No
Operating temperature	-10 to +50°C -10°C (min. Application temperature)
Application temperature (maximum)	+65°C
Relative humidity	≤ 95% noncondensing
Environment	Indoor
IP rating	IP2x

Regulatory

Compliance	CE, REACH, RoHS, WEEE
Certification	CPR
Standards	EN54-5 BS5839-1 Compliant



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 12 June 2024 - 6:13