FC-620-001

Fusion Auxiliary Relay Module

Overview

The FC-620-001 Fusion auxiliary relay module is for use with the FC-610-001 Fusion input / output module, and makes the device capable of switching two mains rated outputs.

Details

- Includes 2x 230 VAC 2A switching relays.

FC-620-001
Fusion Auxiliary Relay Module

Technical specifications

General

Status indication	LEDs
Compatibility	FC-610-001

Electrical

Power supply type	230 VAC
Communication voltage	2.8 to 5 VDC

Output

Output quantity	2
Output type and rating	3.15 A at 250 VAC 50 Hz

Physical

Physical dimensions	160 x 160 x 53 mm (W x H x D)
Colour	Beige
Mounting type	Wall mount
Cable entries	Various - see installation guide (TSD058)

Environmental

Operating temperature	-10 to +55 °C
Storage temperature	5 to 30 °C
Relative humidity	0 to 95% noncondensing
Environment	Indoor

Regulatory

Compliancy	CE, REACH, RoHS 2, WEEE
Standards	EN60950

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 30 July 2025 - 12:53