
P-9910B

DC9000 / Di9000 Series hand held device programmer

General

The P-9910B is the tool for programming and configuration of GST addressable and conventional detectors and devices. It can be used to read parameters and set the operating mode and sensitivities of these devices.



Details

- Hand held & portable
- Easy operation
- 4-digit alphanumeric LCD display
- Low-consumption, hibernation and power saving functions extends the operating time
- Battery low indication

P-9910B

DC9000 / Di9000 Series hand held device programmer

Technical specifications

General

Status indication	LCD display
User interface	LCD display
Compatibility	GST DC-9000E Detectors
Connectivity	I2C & fly leads with clips

Electrical

Batteries	1 x 9 V (Laminated)
Current consumption	≤100 µA (Standby) ≤8 mA (Operating)

Physical

Colour	White
Mounting type	Accessory
Material (body)	Plastic

Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Relative humidity	≤95%, Non-condensing
Environment	Indoor

Regulatory

Compliancy	RoHS, WEEE
Certification	UL

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 12 June 2024 - 6:13