

BS120N

Battery, 12 V, 0,8 Ah



Details

- Maintenance free
- Lead-Calcium grid for extended life
- Wide operating temperature range
- Usable and rechargeable in any position
- Low self-discharge and long service life
- Leakproof construction
- High discharge rate capacity

BS120N

Battery, 12 V, 0,8 Ah

Technical specifications

General

Product type	Sealed lead acid battery
--------------	--------------------------

Electrical characteristics

Nominal voltage	12 V
Nominal capacity	0.8 Ah
Internal approx. resistance	50 mOhm

Charge / discharge

Max. charge voltage	13.8 VDC at +20°C
Max. charge current	0.24 A
Max. discharge current	4 A

Temperature

Charging temperature	0 to +40°C
Discharging temperature	-15 to +50°C

Physical

Physical dimensions	96 x 25 x 62 mm
Net weight	0.371 kg
Shipping weight	0.371 kg
Colour	Dark grey
Material	ABS
Terminal type	Wire Leads

Environmental

Fire retardant	No
Operating temperature	0 to +40°C
Storage temperature	-15 to +50°C

Regulatory

Compliance	CE, RoHS 2, WEEE
Certification	VdS



As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.